

QU∧NTUM DISINFECTION™

Powered by QUA

PERFORMANCE

- all flows up to 44 L/min - up to 740,000 liters of use

WATER DISINFECTION

- eliminates microorganisms up to Log 6 (E. coli, MS2, etc.)

CERTIFICATIONS

Quantum Disinfection[™] is:

a NSF Certified <u>Component</u> to NSF/ANSI 42 for <u>material requirements only</u> (Certificate #: C0292640-01)
tested by IAPMO to NSF/ANSI 61 (Certificate #: 23033)
Certified MOH - China (Certificate #: 2015KF2513)

NO CHEMICALS. NO POWER. NO PATHOGENS

Item Part Number	CT12	
Applications	Point-of-Entry Point-of-Use	
Power Requirements	None	
Quantity of QD ceramics	650 grams	
Maximum Flow *	44 L/min	C
System Dimensions	28 x 8 cm	Powered b
Maximum Pressure **	8.6 bar	
Capacity	740,000 liters	
Water Temperature	5 - 38 °C	
Inlet/Outlet Connections ***	1 inch - FTG / NPT male	0

* The system functions at all water flows up to 44 L/min

E

H

** The system functions at all pressures up to 8.6 bar

*** The system comes with 1 inch NPT connections (FTG type) but we offer a large choice of other FTG connections (see Owner's Manual)

Claire Technologies, LLC Claire Technologies Manufacturing, Inc.



-

sales@clairify-quantum-disinfection.eu

È

https://clairify-quantum-disinfection.eu